



COALA DRY ERASE LAM

Product Information

40 mic gloss finish Biaxially-Oriented polypropylene laminating film

Coated on one side with aqueous acrylic adhesive

Protected by a bleached Kraft release paper coated on one side with a siliconised polyethylene
Ideally suited for application to heat-sensitive output and high ink coverage prints printed on photo gloss paper

The nature of this polypropylene on the Coala Dry Erase Lam makes it ideal for dry-erase presentation boards, schedules, year planners, maps etc.

Technical data

Product Description	
Support	40 mic gloss polypropylen
Adhesive	25 mic Aqueous Acrylic
Liner	One side siliconised polyester
UV Protection Factor	Adhesive contain UV stabilisers, which prevent film degradation and provides UV protection to the underlying image.
Outdoor durability	Up to 2 years
Peel Strength (20 min, FTM1)	11N/25mm
Heat Resistance Range	110 to 120°C
Shelf life	1 year

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme conditions (tropical climate, high humidity, high UV-light exposure or polluted areas) can decrease the durability in a dramatically way.

Shelf Life

Store in closed original packaging in a cool, dry environment 10-25°C with 50% relative humidity
Shelf life of one year if stored in original packaging in recommended conditions

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.





Standard Dimensions

1040 mm x 50 m 1300 mm x 50 m

Recommended settings for Roller Laminator : Temperature 49°C, speed 0.3m to 2.5m per minute

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

