

UPM Raflatac Technical Information

19.01.2011 ENG 561

SELF-ADHESIVE	SHEETS
FACE	PE LASER HS
A4 Filmics	AXN (sales code)
Product	White matt high pigmented computer imprintable polyethylene film.
Use	Information labelling where overprinting is made by laser, digital offset, dot-matrix or thermal transfer. Recommended for drum and logistics labelling. Specially developed for medium and high volume laser printers.

Typical technical values

Substance	104	g/m ²	DIN 53352
Caliper	180	µm	DIN 53370
Elongation MD	430.0	%	DIN 53455
Elongation CD	470.0	%	DIN 53455
Opacity	92	%	DIN 53146/1
Printability	Due to the surface properties, the film is pre-printable by screen, offset, flexography, letterpress, elctrophotography, electrography, digital offset and dotmatrix. Thermal transfer with selected ribbons. Inks for filmic substrates are recommended. Laser and copier printable: specially developed for medium and high volumes.		
Shelf life	Laminate with RP37 adhesive 1 year if stored at room temperature (+20°C, 50% RH) in original packaging and protected from light.		
Warranty	Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use.		

This publication replaces all previous versions. All information is subject to change without notice.



UPM

www.upmraflatac.com